



- ✓ 4 heights, **22 mm.** (GR.2/22), **25 mm.** (GR.2/25), **30 mm.** (GR.2/30) and **35 mm.** (GR.2/35);
- ✓ **can be rolled-up** by assembling the extruded profiles by means of rubber ropes;
- ✓ **rigid**, by means of extruded profiles assembled on plastic (/N) or stainless steel (/S) threaded bars;
- ✓ **linear**, with 2 spacers within the sections;
- ✓ **bendable** by means of a special central elastic spacer which allows the grating to match to the shaped gutters (/C and /B);
- ✓ **curvature upon required sketch**, by means of special spacers (it is necessary to know the radius of the gutter curvature). This type of granting can be only manufactured by using rubber tubes or plastic threaded bars;
- ✓ **different colours** (see the colour chart). Minimum order qty: 100 metres. Special colours upon request.
- ✓ supplied with herringbone **corners** (upon request).
- ✓ GR2/35/S can be used for technical space where are placed filters and pumps.

- ✓ GR2 grate is also suitable where feet are washed before to go in the mosques.

Certified to be **anti-slip** in compliance with DIN 51097 standards.

Manufactured in High Quality **PVC**:

- ✓ **with anti UV additives to prevent** plastic elements from yellowing caused by sunlight;
- ✓ **with anti crash additives to guarantee a better** resistance to shocks;
- ✓ **rot-proof: GR2 is resistant** to micro organisms and bacteria responsible for moulds;
- ✓ **free of Cadmium and Lead**;
- ✓ eco-friendly conformed to RoHS and REACH regulations;
- ✓ Green PVC.

WIDTHS

Art. GR.2/22 – height 22mm.

for linear version and already curved version upon requested sketch: from 175 mm. to 300 mm.
for curvable version: from 150 mm. to 300 mm.

Art. GR.2/25 – height 25 mm.

for linear version and already curved version upon requested sketch: from 175 mm. to 400 mm.
for curvable version: from 150 mm. to 330 mm.

Art. GR.2/30 – height 30mm.

for linear version and already curved version upon requested sketch: from 175 mm. to 500mm.
for curvable version: from 150 mm. to 330 mm.

Art. GR.2/35 – height 35 mm.

for linear version and already curved version upon requested sketch: from 175 mm. to 900 mm.
for curvable version: from 150 mm. to 330 mm.

Roll-up grating: supplied in standard sections 2.5 m. in length.

Rigid grating: supplied in standard sections 1.0 m. in length.

Guarantee: 5 years.

Handcraft gratings for your swimming pool. Grates on measure.



ANTISCIVOLO
ANTISLIP

Summary